



GM Fibre Tape

GM fibre tape is a multi purpose self-adhesive tape for reinforcing joints and patch repairs to plasterboard when gypsum based skim coating is used.

Product-Data-Sheet

Area of Application

Plasterboard walls and ceilings

Key Benefits

Available in a 90m roll
Self adhesive for convenience



Technical Information

Width (mm)	Length (m)	Colour
50	90	White

Storage and Handling

No specific education is required for safe handling. Avoid damp conditions for storage

Packaging

Packaged in an outer cardboard box.

Disposal/Repair

Any excess leftover product can be saved for another project or recycled in accordance with local authority requirements. Fibre Joint Tape which has joint compound on should be disposed of according to the requirements of the joint compound.

Health & Safety

No special precautions are necessary but the use of gloves are recommended during the handling and installation of this product.

Application/Installation

To use to complete tape and jointing finishes to tapered edge plasterboard: Apply the self-adhesive tape to the board joint, then cover the tape with a minimum of 1mm of GM Joint filler to the shoulder of the taper. GM Fibre tape is recommended as part of a full GM system,



**RIGHTS OWNED IN THAILAND BY
GYPMAN TECH COMPANY LIMITED**

9/9 @Sathorn building Floor 16 Zone A, Sathorn Tai Rs,
Yannawa, Sathorn, Bangkok 10120 Thailand

GM FIBRE TAPE
GYPSUM